





MFD BY CHRYSLER CORPORATION DATE OF MFR 6-97 GUWR 2405 KG(5300 LB)
GWR FRONT WITH TIRES RIMS AT 16X7.0 COLD
1248 KG(2750 LB) P225/70R16
GWR REAR WITH TIRES RIMS AT 16X7.0 COLD
1339 KG(2950 LB) P225/70R16 248 KPA(36 PSI) 248 KPA(36 PSI)
THIS VEHICLE CONFORMS TO ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY
STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN: 1J4GZ78S4VC759625 TYPE: MPV SINGLE X DUAL



MDH: 060619 600 PNT:PR4 VEHICLE MADE IN U.S.A. TRM:CLRZ 4648583

BY
CHRYSLER
CORPORATION

DATE OF MFR
6-97

GUWR
2405 KG(5300 LB)

GWM FRONT,

1248 KG(2750 LB)

GWM REAR

1355 KG(2950 LB)

WITH TIRES

P225/70R16

RIMS AT

16X7.0

COLD

248 KPA(36 PSI)

WITH TIRES

P225/70R16

RIMS AT

16X7.0

COLD

248 KPA(36 PSI)

THIS VEHICLE CONFORMS TO ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY
STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

FIM: 1J4GZ78S4VC759625

TYPE:

MPV

SINGLE X DUAL

NOM:

060619 600

PNT:PR4

VEHICLE MADE IN U.S.A. TRM:CLAZ 4648503

MFD BY
CHRYSLER
CORPORATION

DATE OF MFR
6-97

GEAR FRONT,
WITH TIRES
1248 KG(2750 LB) P225/70R16 RIMS AT 16X7.0 2405 KG(53000 LB)
COLD

GEAR REAR
WITH TIRES
1339 KG(2950 LB) P225/70R16 RIMS AT 16X7.0 248 KPA(36 PSI)
COLD


THIS VEHICLE CONFORMS TO ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY
STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN: 1J4GZ78S4VC759625

TYPE:

HPU

SINGLE X DUAL



DMV:

060619 600 PNT:94

VEHICLE MADE IN U.S.A. TON:CLQZ 46498503

MFD BY CHRYSLER CORPORATION DATE OF MFR 6-97 GVWR
GAUR FRONT WITH TIRES RIMS AT 16X7.0 2405 KG(5300 LB)
1248 KG(2750 LB) P225/70R16 COLD
GAUR REAR WITH TIRES RIMS AT 16X7.0 248 KPA(36 PSI)
1339 KG(2950 LB) P225/70R16 COLD
248 KPA(36 PSI)

THIS VEHICLE CONFORMS TO ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY
STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN: 1J4GZ78S4VC759625 TYPE: MPV SINGLE X DUAL



MDH: 060619 600 PNT:PR4 VEHICLE MADE IN U.S.A. TRM:CLRZ 4648583